

FSP2500-57APB

Features

- Certified CB 62368-1
- 80 Plus 230V EU Platinum Efficiency
- Intel Design ATX 12V V3.1
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

SAFETY STANDARD APPROVAL



DESCRIPTION

FSP 57APB Series features with eco-friendly design, which allows 57APB series to reach up to 94% efficiency. 57APB series also equipped with complete protection to prevent your system from damage. 57APB series does the job efficiently and reliably, making it a stable power supply unit built to satisfy the demands of all kind of system build.

GENERAL SPECIFICATIONS

Dimension:	200 x 150 x 86 (mm)	Environment	
(L x W x H)	7.87 x 5.91 x 3.39 (inch)	Working temperature:	0°C to 50°C
Efficiency:	80 Plus 230V EU Platinum Efficiency	Storage temperature:	-40°C to + 70°C
Hold-up time:	230V / 50Hz: ≥ 16ms	Working humidity:	~90% RH non-condensing
Operating altitude	5,000 meters above sea level	Storage humidity:	~90% RH non-condensing
MTBF:	100,000 hours of continuous operation at 25°C, Max. output load		

INPUT SPECIFICATIONS

Input voltage:	200-240Vac
Input frequency:	50-60Hz
Input current:	230 Vac @ 15A

OUTPUT RATING

Outputs	+3.3V	+5V	+12V	-12V	+5Vsb
Max	25A	25A	208.3A	0.3A	4A
Min.	0A	0A	0A	0A	0A
Regulation	±3%	±3%	±3%	±10%	±4%
Ripple/Noise	30 mV	30 mV	70 mV	100 mV	35 mV

- (1) The +3.3V and +5V total output shall not exceed 125W.
- (2) Maximum combined current for the +12V outputs shall be 208.3A.

MECHANICAL SPECIFICATIONS

